

NEW

I.T.E.



65 Watt Series

Desktop Type

ATS065A1 - □ X X X

A : C8
G : C6
P : C14

O / P Voltage



Features :

- IEC/EN/UL 62368-1 3rd Edition
- 100-240VAC Universal Input
- Regulated Output With Low Ripple Noise
- Safety Agency Requirements and EMI/EMS Certified
- Modified and Custom Design Available
- 1 Year Warranty

Model	O/P Voltage	O/P Current	Watt
ATS065A1-□120	12.0V	5.00A	60W
ATS065A1-□150	15.0V	4.34A	65W
ATS065A1-□160	16.0V	4.07A	65W
ATS065A1-□180	18.0V	3.62A	65W
ATS065A1-□190	19.0V	3.43A	65W
ATS065A1-□240	24.0V	2.71A	65W
ATS065A1-□480	48.0V	1.36A	65W
ATS065A1-□560	56.0V	1.17A	65W

Input	
Voltage	100-240VAC
Line Frequency	50-60Hz
Current	1.4A Max.
Protection	Internal Primary Current Fuse
Configuration	IEC60320/C6,C8,C14

Output	
Load Regulation	±5% (Typical)
Ripple & Noise	1% Vp-p Max. for Output Voltage@ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection

Electrical	
Topology	Switching Flyback
Dielectric Withstand	3000VAC Primary - Secondary
Leakage Current	0.25mA @ 2Pin / 3.5mA @ 3Pin
Efficiency	DoE Level VI, ErP Stage 2
EMC Standards	EN55032
	EN61000-3-2,3
	EN55035
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

Environmental	
Operating Temperature	-20 to + 40°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH
	Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

Mechanical	
Case Dimension	L115 x W48.5 x H31.6 (mm)
Weight	220g (Ref.)